

Hesse REMOVER OS 5600

>Product description

A highly effective, water-based cleaning concentrate, for removing old care products from sealed parquet and wooden floors.

>Areas of application

Removes residues of Hesse AQUA-REFRESHER, PROTECT-CLEANER and similar care products, as well as stubborn stains and footprints.

>Surface Preparation

Surface preparation	Remove adhering particles from the surface to be cleaned with a cloth or a soft brush.
Finishing	After complete drying of the residue-free cleaned surface, a new care treatment or suitable surface treatment is required! The surface must be absolutely dry before further work with care products or suitable surface treatments; recommendation: If possible, leave to dry overnight at 20°C with adequate air circulation. Final treatment: after correct pre-treatment, surface coating with customer-specific products.

>Application

Application
other treatment
other treatment

>Processing instructions

Einschichtiger Auftrag. Hesse REMOVER OS 5600 is diluted with water according to the degree of soiling and the surface to be cleaned is wiped evenly damp. Initial cleaning: approx. 1 l of Hesse REMOVER OS 5600 to 5 l of cleaning water. Mop the floor with this cleaning solution and leave to infiltrate for 5 minutes. The application quantity and infiltration time should be gauged so that no swelling of the wood occurs! Then mop the surface again with clean water to remove the dissolved coating and any potential remover residue. Make sure that the surface does not get too wet during mopping!

>Technical data

Flow time	31 s / DIN EN ISO 2431 - 3 mm
Appearance	colourless
Density series kg/l	1.016
Giscode	GE20
Form of delivery	fluid
Non-volatile content series %	12.3
VOC EU %	9 %
VOC FR	C
Storage temperature	10 - 40 °C
Shelf life in weeks	104
Working temperature	20 °C

>Ordering information

Order number	Container Size
OS 5600	1 l, 5 l, 25 l

Hesse REMOVER OS 5600


>Particular instructions

A highly effective, water-based cleaning concentrate, for removing old care products from sealed parquet and wooden floors. Removes residues of Hesse AQUA-REFRESHER, PROTECT-CLEANER and similar care products, as well as stubborn stains and footprints. For large surfaces, it is recommended to divide the surface into subsection. The suitability of the substrate for the use of Hesse REMOVERS OS 5600 should be tested in one location before a full surface application. The cleaning effect for specific contaminants should also be tested. Experience suggests that stains that are already present on the existing surface of the coating, or that have already infiltrated into the wood, can no longer be completely removed by subsequent cleaning and maintenance. After complete drying of the residue-free cleaned surface, a new care treatment or suitable surface treatment is required. Caution: too much water and/or too long an exposure can cause the wood to swell and damage it. Therefore, after work performed by professionals whenever possible. REMOVER residues left on the surface affect the adhesion of subsequent care products. Keep locked away and out of the reach of children! Containers should only be put out for recycling when they have been completely emptied.

>General information

Distribute uniformly thinly over the floor with a suitable mop, or similar. Alternatively, after applying the cleaning solution and the appropriate infiltration time, it is also possible to work with a single-disc orbital sander with white pad, to remove the dirt. Here to the floor must then be cleaned with clear water to ensure that all the dirt is removed. When large amounts or care product residues or other contamination are to be removed, this procedure can be repeated if necessary.

>Particular properties and/or testing standards

Test standard / basis	Testing laboratory	Mark	Report	No.
Formulation is free of: wood preservatives, toxic heavy metals, phthalate plasticizers, formaldehyde, CMR substances in Categories 1A + 1B and volatile aromatic and halogenated organic compounds.	HESSE			

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.hesse-lignal.de or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.